


Home




Search







MicroPatent® Worldwide PatSearch: Record 1 of 1



	1811	121 گستر	.3 121 /	1214 /	1218
ሴ ን	ネットワータ アドレス	ポート	デパイ # タイプ	<i>ምペ</i> ብ አ ዚ ርጋ	
	1321.16.120	NUL	LBP	Ready	2000 AF 7 4
	152,1,16,150	MUIL	Cepter	J&B	Serbe r
	808	640	ಬರಕ	404	
	1230 街回記出 デバイ ステーブル				


Family Lookup

JP11346216 DEVICE AND METHOD FOR MANAGING NETWORK DEVICE AND RECORD MEDIUM CANON INC

Inventor(s): ;HAMADA NOBORU ;SUGIYAMA AKIRA Application No. 11015491, Filed 19990125, Published 19991214

Abstract:

PROBLEM TO BE SOLVED: To solve the congestion of a network traffic only by transmitting only a packet truly necessary in a retrieval sequence by using a stored value when the value is stored in a storage means as plural device characteristics related with a device detected by retrieval.



SOLUTION: Only information changeable with a time is obtained at the time of retrieval after the second time for a network device whose information is obtained at the time of the first retrieval. Also, the information obtained at the time of the first retrieval is copied and used for the unchangeable information so that information capture or response communication cannot be operated at the time of retrieval after the second time. Relating to this device, the information of the detected network device is registered in a detecting device table 1220. For example, the network address of the detected network device is registered in a network address column 1201, and a port value returned by an MIBOpen function is registered in a port column 1202.

Int'l Class: H04L01224 H04L01226 G06F01300 G06F01300 H04L01228

Priority: JP 10 61659 19980312 JP 10 87646 19980331

MicroPatent Reference Number: 000687478

COPYRIGHT: (C) 1999 JPO









itentWeb Edit Home Search

Return to Patent List

•

For further information, please contact:

<u>Technical Support | Billing | Sales | General Information</u>

